

QA4 Specifications



AneticAid

QA4 Specifications

Standard Features

	Powered Height adjustable - Height range 26.5" - 42.5"
	Powered Backrest - Adjustable
	Powered Lateral Tilt - Electrically operated 12º left or right
	Powered Trendelenburg - Electrically operated 20° Trend / 12° reverse Trend
	Powered Sliding Top - Allows greater surgical access to both head and foot end
	Articulating Headrest - Removable, interchangable with dual articulation
	Full length siderails - Folding and removable
_	Light Weight Removable Foot Section - Removable, push button release and self locking mechanism
	Surgical Accessory Rail - Stainless steel, USA standard, suitable for all operating
_	Latest Caster Technology - Twin wheel casters assist with an exceptionally stable surgical platform
	5th Wheel Steering - Easily guided by one person
_	Advanced Breaking System- Operated from either side, braking all 4 casters simultaneously
	Pushing Handles - Ergonomically positioned
_	IV Pole - Innovative quick release, safety locking mechanism
	Cylinder Trough - E-size, side loading
	K8 Pressure Care Mattress - Viscoelastic foam, anti-bacterial and latex free
	Infection Control - Anti-bacterial properties and smooth molded surfaces

Dimensions

Overall Length	82.7"
Overall Width (brakes off)	32.9"
Maximum Weight	550 lbs
Minimum Height	26.5"
Maximum Height	42.5"





3 YEAR WARRANTY TERMS AND CONDITIONS APPLY







Document number: 93059i/1/090914